

Quad ESL 2812 Głośniki Elektrostatyczne Salon Poznań Wrocław

Cena: 118 337 Kč

VLASTNOSTI

POPIS VÝROBKŮ

Specyfikacja:

Gwarancja: Polskiego Dystrybutora 2 lata

Dostępne kolory: Czarny

Cena za sztukę

Głośnik elektrostatyczny

Dane techniczne:

Format: Floor standing dipole with 3° fixed tilt black

Type: Multiple Electrostatic Drive Membranes

Membrane: Ultra Low Mass (0.5gm) Tensioned Film

No. of Panel Elements: 4

Time Delay: Progressive Concentric Rings

Chassis Structure: Heavy Duty Composite Aluminium / Steel

Maximum Output: 2 N/m² at 2m on axis

Sensitivity: 1.5 mbar per volt referred to 1m (86dB/2.83V RMS equivalent)

Impedance: 8 Ohms nominal

Impedance Variation: 4 - 15 Ohms

Maximum Input: Continuous input voltage (RMS): 10V

Programme Peak for undistorted output: 40V

Permitted peak input: 55V

Frequency Reponse: 37Hz - 21kHz (-6dB) 33Hz - 23kHz (useable)

Directivity Index: See Polar Diagrams

Distortion (100dB @ 1M): Above 1000Hz 0.15%, Above 100Hz 0.5%, Above 50Hz 1.0%

Directivity Index: See Polar Diagrams

AC Input: 220 - 240V or 110-120V

Power Fuse: 63 mA anti-surge, 200-240V, 100 mA anti-surge, 100-120V

Power Consumption : 6W

Wymiary produktu: 1040 x 695 x 385 mm

Waga netto: 34.80 kg