

Luxman L-505uX II Mark II Wzmacniacz Zintegrowany Salon Poznań Wrocław



Cena: 143 106 Kč

Gwarancja: Producenta 2 lata

Dostępne kolory: Srebrny

VLASTNOSTI

Wyjścia głośnikowe: , A+B

POPIS VÝROBKŮ

Zintegrowany Wzmacniacz Luxman L-505uXII Mark II

The attraction of the L-505uXII is its new level of refinement, approaching perfection as an authentically desirable product

The L-505uXII is the eagerly awaited Mark II version of the popular L-505uX that has been at the forefront of pre-amplifier design since its launch in 2011. Incorporating an abundance of proprietary technologies, such as Luxman's Version 4.0 ODNF (Only Distortion Negative Feedback), as well as LECUA (Luxman Electronically Controlled Ultimate Attenuator), this product is a truly multifunctional integrated amplifier. As Luxman's latest high-end model, the L-505uXII continues the evolution of the L-505 series, which has attracted many fans of audio quality and earned a great reputation. As an amplifier which exudes sophistication and authenticity beyond its class, the L-505uXII represents the latest in a long line of exemplary models.

ODNF* Version 4.0 - Innovative amplification feedback circuit

An integral part of the design of the L-505uXII is LUXMAN's original ODNF amplification feedback circuit featuring a high-speed primary slew rate, an ultra-wide bandwidth and a low level of distortion that is achieved by feeding back only the distorted components of the audio from the amplifier's output circuit. The L-505uXII is equipped with the latest Version 4.0 ODNF circuit, resulting in a dramatically enhanced accuracy in distortion detection due to the paralleled first stage and Darlington equipped second stage amplification circuit, as well as a paralleled first stage error detection circuit. With its lower impedance and higher S/N ratio, the L-505uXII realizes accurate reproduction of even the gentlest audio signals and achieves a full range of dynamic musical expression. The output stage, with its parallel push-pull structure, has secured sufficient power at 100W+100W(8Ω) and 150W+150W(4Ω).

Highly accurate LECUA computerized attenuator

LECUA (Luxman Electronically Controlled Ultimate Attenuator) is at the heart of the pre-amplifier section and the sound volume adjustment function of the L-505uXII. The L-505uXII design also uses a solid state(IC) type circuit to achieve a significant reduction in size. LECUA provides an ideal level control mechanism that allows smooth and fine volume adjustment over 88 steps, thereby minimizing any deterioration of the audio signal. In addition, left and right balance adjustment is integrated into the attenuator's control functions. The multifunctional ability of LECUA ensures accuracy over

the full range of the volume control, whilst suppressing any deterioration of sound quality. The volume may also be adjusted with the remote control, but when adjusting the volume manually, the tactile design and gradual motion of the control itself enables intuitive adjustment of the attenuation level.

Discrete buffer circuit

The L-505uXII features a new discrete buffer circuit in the output stage of the pre-amplifier circuit that is equivalent to the type used in our high-end C-900u separate amplifier. The pre-amp output stage is able to drive the signal with enhanced current supply capacity. The clarity of the audio signal is protected, whilst at the same time, the driving force fed through to the power amplifier stage is significantly increased. The power and reproduction capability of the L-505uXII achieves overwhelming scale sensitivity and a sharpness on start-up that cannot be achieved by conventional pre-amplifiers.

High stability power supply

The power supply of the L-505uXII consists of an EI core type power transformer, highly regulated, with four large capacity 10,000 μ F blocking capacitors creating a highly stable power supply. This ensures an instantaneous, constant and stable current supply.

Low impedance transmission

Large-capacity, low resistance speaker relays are connected in parallel to enable lossless transmission for the powerful driving force that is generated by the large-scale output circuit. In addition, the damping factor has been improved from 180 to 210 by lowering the impedance of the wiring pattern.

Original technologies prioritize sound quality

To realize a smooth, stress free signal transmission LUXMAN use an original Beeline construction that features a non-angled wiring pattern to allow smooth signal transmission along the shortest optimal route. This is one of many examples of a LUXMAN original design that makes sound quality a priority.

A wide variety of custom-made components for high sound quality components for high sound quality

OFC cabling is used in the internal wiring of the L-505uXII, achieving natural signal transmission due to the spirally wrapped shielding on each non-plated wire core. A high quality input selector IC is employed to improve separation and eliminate crosstalk. This model is generously equipped with many custom-made parts designed to achieve high sound quality such as in-line layout speaker terminals for easier speaker cable connection.

An abundance of user-friendly functions

The L-505uXII is equipped with a high quality phono pre-amplifier that is compatible with MM and MC cartridges supporting full analog reproduction. This model offers all the functions that a high quality pre-main amplifier should offer such as bass/treble tone control, L/R balance adjustment using LECUA, pre/power separation function, volume function and headphone output to name a few.

Specyfikacja

Rated output

110W + 110W (8 Ω),
210W + 210W (4 Ω)

Input sensitivity/input impedance

PHONO (MM): 2.5mV/47k Ω
PHONO (MC): 0.3mV/100 Ω
LINE: 180mV/47k Ω

BAL.LINE: 180mV/55kΩ

MAIN-IN: 1.05V/47kΩ

Output voltage

REC OUT: 180mV, PRE-OUT: 1V

Frequency response

PHONO: 20Hz to 20kHz (± 0.5 dB)

LINE: 20Hz to 100kHz (within -3dB)

Total harmonic distortion

0.007% or less (8Ω, 1kHz)

0.08% or less (8Ω, 20Hz to 20kHz)

S/N ratio (IHF-A)

PHONO (MM): 91dB or more

PHONO (MC): 75dB or more

LINE: 105dB or more

Volume adjustment

New LECUA1000

Amplification circuit

ODNF 4.0

Output configuration

Bipolar 3-parallel push-pull

Damping factor

260

Max. amount of tone control

BASS: ± 8 dB at 100Hz

TREBLE: ± 8 dB at 10kHz

Power supply

230V~(50Hz) / 115V~(60Hz)

Power consumption

350W

86W (under no signal), 0.4W (at standby)

External dimensions

440(W) x 178(H) x 454(D) mm

front side knob of 20mm and rear side terminal
of 27mm included in depth

Net weight

25.0kg (main unit)

Accessories

Remote control (RA-17A)

Power cable

Speaker terminal Supported Y-lug terminal dimension

Width of part a: 15mm or less

Width of part b: 8mm or more

* Connection may not be performed
depending on the shape of the
Y-lug terminal.