


## Esoteric Grandioso G1 Generator Sygnału Zegarowego Salon Poznań Wrocław



Cena: 709 467 Kč

Gwarancja: Polskiego Dystrybutora 2 lata

Dostępne kolory: Srebrny

### VLASTNOSTI

Wysokość (cm): 13, 1

Szerokość (cm): 44, 5

Głębokość (cm): 36

Waga (kg): 13

### POPIS VÝROBKŮ

## Generator Sygnału Zegarowego Esoteric Grandioso G1

Clock outputs CLOCK OUT 44.1 kHz setting 44.1, 88.2, 176.4, 352.8, 705.6 kHz 1.4112, 2.8224, 5.6448, 11.2896, 22.5792 MHz 48 kHz setting 48, 96, 192, 384, 768 kHz 1.536, 3.072, 6.144, 12.288, 24.576 MHz Both settings 100 kHz, 10 MHz Connectors BNC coaxial (75 Ω) Output level Rectangular wave (TTL level / 75 Ω) 10MHz OUT 10 MHz Connectors BNC coaxial (50 Ω) Output level Sine wave :  $0.5 \pm 0.1$  Vrms / 50 Ω Master clock input Input frequency Rb+EXT1pps mode 1pps signal (GPS precision or better) Rb+EXT10M mode 10MHz (GPS precision or better) EXT 10M-IN mode 10 MHz (within  $\pm 10$  ppm) Connector BNC coaxial (50 Ω) Input levels 10MHz Sine wave: 0.5-1.0 Vrms/50 Ω Square wave: 1.5-3.0 Vpp/50 Ω 1pps signal Positive pulse, TTL level/100 kΩ Output clock stabilization (approximate time in minutes) Until oscillator stabilizes after power turned on 10 PLL locking time 1 Frequency stability Within  $\pm 0.1$  ppb (-20°C to +65°C) Frequency precision Within  $\pm 0.05$  ppb (when shipped new) General Power supply AC 230V, 50Hz AC 120V, 60Hz AC 220V, 60Hz Power consumption 85W (while warming up) 28 W (when stable) Dimensions (W x H x D) (including protrusions) 445 x 131 x 360 mm (17 1/2" x 5 1/8" x 14 1/8") Weight 13kg (28 1/2 lbs) Included accessories Power cord x 1, Owner's manual x 1, Warranty card x1