

## Esoteric N-01XD Streamer Odtwarzacz Sieciowy Salon Poznań Wrocław



Cena: 661 694 Kč

Gwarancja: Polskiego Dystrybutora 2 lata

Dostępne kolory: Srebrny

### VLASTNOSTI

Dostęp do sieci: Wi-Fi, Ethernet (LAN)

Funkcje sieciowe: Bluetooth, DLNA, AirPlay, Spotify, Tidal, Sterowanie z aplikacji mobilnej

Główne połączenia - Wejścia/Wyjścia: Wejście USB 2, XLR 0/1, Analogowe audio 0/1, Cyfrowe Optyczne 1/0

Wysokość (cm): 16.2

Szerokość (cm): 44.5

Głębokość (cm): 43.8

Waga (kg): 25.7

Wejście USB-B DAC: Nie

### POPIS VÝROBKŮ

## Streamer Odtwarzacz Sieciowy Esoteric N-01XD

### Dane techniczne:

Digital audio input ES-LINK 1 (L/R) Input signal formats Linear PCM 44.1k to 768kHz, 48bit (ES-LINK5 format) DSD 2.8MHz, 5.6MHz, 11.2MHz, 22.4 XLR 1 Input level 5.0Vp-p Input impedance 110Ω Input signal formats Linear PCM 32k to 192kHz, 16bit / 24bit (AES/EBU format) DSD 2.8MHz (ES-LINK1, ES-LINK2, DoP format) RCA 1 Input level 0.5Vp-p Input impedance 75Ω Input signal formats Linear PCM 32k to 192kHz, 16bit / 24bit (IEC60958 format) DSD 2.8MHz (DoP format) OPTICAL 1 Input level -24.0 to -14.5dBm peak Input signal formats Linear PCM 32k to 192kHz, 16bit / 24bit (IEC60958 format) DSD 2.8MHz (DoP format) USB 1 (B type) Input signal formats Linear PCM 44.1k to 384kHz, 16bit / 24bit / 32bit

DSD 2.8MHz, 5.6MHz, 11.2MHz, 22.5MHz ETHERNET 1 (1000BASE-T) Input signal formats Linear PCM 44.1k to 384kHz, 16bit / 24bit / 32bit (stereo)

• 32bit audio files only support integer formats. DSD 2.8MHz, 5.6MHz, 11.2MHz, 22.5MHz (stereo) Supported file formats PCM lossless FLAC, Apple Lossless (ALAC) , WAV, AIFF, MQA DSD lossless DSF, DSDIFF (DFF) , DoP Compressed audio MP3, AAC (m4a container) USB DRIVE 2 (Front, Rear) Supported file formats FAT32, NTFS, Single partition; USB 2.0 or faster recommended maximum Power Supply 0.5A Input signal formats Linear PCM 44.1k to 384kHz, 16bit / 24bit / 32bit (stereo)

• 32bit audio files only support integer formats. DSD 2.8MHz, 5.6MHz, 11.2MHz, 22.5MHz (stereo) Supported file formats PCM lossless FLAC, Apple Lossless (ALAC) , WAV, AIFF, MQA DSD lossless DSF, DSDIFF (DFF) , DoP Compressed audio MP3, AAC (m4a container) Analog audio outputs XLR/ESL-A 1 pair (L/R) Output level 5.0Vrms (1kHz, 10k $\Omega$  loaded) Output impedance 40 $\Omega$  RCA 1 pair (L/R) Output level 2.5Vrms (1kHz, 10k $\Omega$  loaded) Output impedance 15 $\Omega$  Clock sync input BNC 1 Input frequency 10MHz ( $\pm$ 10ppm) Input impedance 50 $\Omega$  Input level Rectangle wave equivalent to TTL level Sine wave 0.5 to 1.0Vrms Clock sync output BNC 1 Output level TTL level equivalent (75 $\Omega$  load) Output frequency 44.1k / 48kHz Output frequency accuracy  $\pm$ 0.5ppm General Power supply AC 230V, 50Hz AC 120V, 60Hz AC 220V, 60Hz Power consumption 38W External dimensions (WxHxD) 445 x 162 x 438mm 17- $\frac{5}{8}$ " x 6- $\frac{1}{2}$ " x 17- $\frac{1}{4}$ " (including protrusions) Weight 26.3kg / 58 lb Included accessories Power cord x 1 HDMI cable x 1 Felt pads x 4 Owner's manual x 1 Warranty card x 1

## Audio performance

Frequency response 5Hz to 70kHz (-3dB) S/N ratio 113dB Distortion 0.0007% (1kHz)